



**CORPORATE
OFFICE**

P.O. Box 558
317 Davisville Road
Willow Grove, PA 19090
Phone: 267-913-0002
Fax: 267-913-0510

**BEAVER SPRINGS
PLANT**

RD1 Box 189
Sawmill Road
Beaver Springs, PA 17812

**LEHIGHTON
PLANT**

523 Mill Road
Lehigh, PA 18235

**ALLENTOWN
PLANT**

6047 Adams Lane
Allentown, PA 18109

For information about this content or other products and services contact: Bill Schneider at 1-800-725-5385 or e-mail to bill.schneider@remmey.com

GUIDELINES FOR SAFE & EFFICIENT WOOD WASTE REMOVAL

Here are some helpful guidelines for properly preparing wood waste and pallets for shipping.

1. Wooden Pallets Only - remove all banding, corrugated, and stretch wrap film.
2. All stacks need to be no greater than 7 feet high.
3. Stack pallets according to size - largest on bottom to smallest on top layer.
4. Remove all loose and unattached lumber from inside or in between pallets.
5. Stack all loose lumber on a pallet or place in Gaylord containers.
6. Place (1) steel or plastic strap around each stack, strapping top to bottom.
7. Pallets need to be stacked, strapped and ready to load when we arrive. We allow 45 minutes to get loaded.

These guidelines will make the transportation of wood waste and pallets as safe as possible during highway travel.

If you have any questions, please do not hesitate to call Ted Feather at 267-913-0002 or e-mail Ted at Ted.Feather@remmey.com

Leaders in Design, Manufacturing and Service

www.remmey.com